

FAST

RATIONALITY AND SYNTHESIS  
OF TECHNOLOGY FOR HIGH-PERFORMANCES  
APPLICATIONS



Technical Specs		FAST
Maximum width of the product	mm	120
Maximum height of the product	mm	60
Bag length (min/max)	mm	80/250
Maximum reel width	mm	400
Max Speed	p.p.m.	600
Wrapping material	heat & cold sealable materials	

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.



PLANET A

THE NEW FRONTIER  
OF THE ESSENTIAL



Technical Specs		PLANET A	PLANET B
Maximum width of the product	mm	180	180
Maximum height of the product	mm	100	100
Bag length (min/max)	mm	80/530	80/530
Maximum reel width	mm	500	500
Max Speed	p.p.m.	60/120	60/120
Wrapping material	heat & cold sealable materials		

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.

PLANET B

INVERTED SIMPLICITY



Passion, expertise and an unwavering commitment to exceeding customer expectations drive everything we do. In the world of packaging machinery, the human element remains at the heart of our innovation.

We believe that a wrapper's true value lies not just in its performance but in how seamlessly it integrates into real-world operations. Every customer is a partner, bringing visions to life while we transform ideas into intelligent, efficient and future-ready solutions: designed, tested and optimized for success.

Every project is a step toward continuous improvement. Our machines are more than just equipment; they are intuitive, reliable and cost-effective tools designed to simplify operations and empower the people who use them every day. By leveraging cutting-edge technology, we optimize performance, enhance efficiency and minimize energy consumption without ever losing sight of the people behind the process.

Because true innovation isn't about complexity:  
it's about making things work better. Simplicity is the ultimate sophistication.



PACK  
IT YOUR  
WAY

FOOD  
& NON FOOD  
PACKAGING

MOTION A

DEAL WITH SIMPLICITY  
IN COMPLICATED APPLICATIONS



MOTION B

HIGH PERFORMANCES, FLEXIBILITY  
AND HERMETIC SEALING IN A SINGLE  
SOLUTION



MOTION HP

HIGH PERFORMANCES,  
FLEXIBILITY AND HERMETIC SEALING  
IN A SINGLE SOLUTION



Technical Specs	Motion A	Motion B	Motion HP
Maximum width of the product	mm	320	320
Maximum height of the product	mm	120	120
Bag length (min/max)	mm	80/600	80/600
Maximum reel width	mm	750	650
Max Speed	p.p.m.	80	80
Wrapping material	heat & cold sealable materials, compostable, paper and recyclable film		

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.





HORIZONTAL PACKAGING MACHINES

DISKO

COMPACT AND COMPLETELY AUTOMATIC



Technical Specs		DISKO
Maximum width of the product	mm	40
Maximum height of the product	mm	30
Bag length (min/max)	mm	47/75
Maximum reel width	mm	150
Max Speed	p.p.m.	1500
Wrapping material		heat & cold sealable materials

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.



AUTOMATIC INTEGRATED SYSTEMS



HORIZONTAL PACKAGING MACHINES

COSMIC

ROBUSTNESS AND FLEXIBILITY OF USE TO REMOVE THE ENTRY LEVEL CONCEPT



Technical Specs		COSMIC
Maximum width of the product	mm	250
Maximum height of the product	mm	120
Bag length (min/max)	mm	50/600
Maximum reel width	mm	650
Max Speed	p.p.m.	150
Wrapping materials		heat & cold sealable materials

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.



WIDE B

THE ALTERNATIVE FOR DIFFICULT PRODUCTS



Technical Specs		WIDE B
Maximum width of the product	mm	250
Maximum height of the product	mm	120
Bag length (min/max)	mm	50/600
Maximum reel width	mm	650
Max Speed	p.p.m.	80
Wrapping material.		heat & cold sealable materials, compostable, paper and recyclable film

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.



4S

4-SIDE SEAL PROFILE, ROBUST IN NATURE, A DIFFERENT CONCEPT OF PACKAGING



Technical Specs		4S
Maximum width of the product	mm	250
Maximum height of the product	mm	120
Bag length (min/max)	mm	50/600
Maximum reel width	mm	650
Max Speed	p.p.m.	150

The data serves as a guideline; each machine can be entirely adapted to the customer's specific requests.

